

V•ROD 45 HYBRID PE

Product Data Sheet - V•ROD 45 HYBRID PE

REVISION: APRIL 2018

	#3	#4	#5	#6
Nominal Diameter Area	3/8 in (.110in ²)	1/2 in (.196 in ²)	5/8 in (.307in ²)	3/4 in (.442 in ²)
Lengths	Up to 55 ft	Up to 55 ft	Up to 55 ft	Up to 55 ft
Weight	.063 lb/ft	.112 lb/ft	.260 lb/ft	.366 lb/ft
Ultimate Tensile Strength ASTM 7205	131 ksi 900 MPa	131 ksi 900 MPa	131 ksi 900 MPa	131 ksi 900 MPa
Tensile Modulus of Elasticity ASTM 7205	6 527 ksi 45 GPa	6 527 ksi 45 GPa	6 527 ksi 45 GPa	6 527 ksi 45 GPa
Guaranteed Transverse Shear Capacity ASTM 7617	21.1 ksi 145.5 MPa	21.1 ksi 145.5 MPa	21.1 ksi 145.5 MPa	21.1 ksi 145.5 MPa
Moisture Content ASTM D570	<.5 %	<.5 %	<.5 %	<.5 %
Fiber Content	>80 % by weight	>80 % by weight	>80 % by weight	>80 % by weight



PULTRALL

700, 9 Rue Nord, Thetford Mines (Quebec) G6G 6Z5 CANADA
Phone: 418 335-3202 | Fax: 418 335-5117 | www.vrod.ca